

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 1/11

FSG-Acetone

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

FSG-Acetone

Other means of identification:

Aceton

Article No.:

AC10000

Index No.:

606-001-00-8

CAS No.:

67-64-1

REACH No.:

01-2119471330-49

EC No.:

200-662-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Cleaner

1.3. Details of the supplier of the safety data sheet

distributor:

FSG Schäfer GmbH

Boschstraße 14

48703 Stadtlohn

GERMANY

Telephone: +49 (0) 25 63 - 93 95 - 0

Telefax: +49 (0) 25 63 - 93 95 - 25

E-mail: verkauf@fsg-schaefer.de

Website: www.fsg-schaefer.de

E-mail (competent person): sdb@fsg-schaefer.de

Only for information: National Poisons Information Service (Birmingham Unit): 844 892 0111

1.4. Emergency telephone number

24h: Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department., Office FSG: +49 (0) 2563 93950. (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 2/11

FSG-Acetone

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

Hazard statements for physical hazards

H225 Highly flammable liquid and vapour.

Hazard statements for health hazards

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 67-64-1 EC No.: 200-662-2 Index No.: 606-001-00-8 REACH No.: 01-2119471330-49	acetone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	≥ 90 - ≤ 100 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove affected person from the danger area and lay down. Remove contaminated, saturated clothing immediately.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 3/11

FSG-Acetone

Following inhalation:

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. If unconscious but breathing normally, place in recovery position and seek medical advice.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration hazard: Pulmonary oedema, Pneumonia. Harmful: may cause lung damage if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Subsequent observance for pneumonia and lung oedema. Where appropriate artificial ventilation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Dry extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air. Reignition possible over considerable distance.

Hazardous combustion products:

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear protective gloves/protective clothing/eye protection/face protection. Cool endangered containers by spraying with water. Heating causes rise in pressure with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

5.4. Additional information

not determined.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Provide adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Processing vapours can irritate the respiratory tracts, skin and eyes.

Protective equipment:

Personal protection equipment: see section 8.

6.1.2. For emergency responders

Personal protection equipment:

Use personal protection equipment. Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 4/11

FSG-Acetone

6.3. Methods and material for containment and cleaning up

For containment:

Methods and material for containment and cleaning up: In case of fire, use extinguishing powder or sand. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Dispose of waste according to applicable legislation.

For cleaning up:

Clean with detergents. Avoid solvent cleaners.

6.4. Reference to other sections

Disposal: see section 13.

Personal protection equipment: see section 8.

6.5. Additional information

not determined.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Store in a well-ventilated place. Keep container tightly closed. Use personal protection equipment. Do not breathe gas/fumes/vapour/spray. Remove contaminated, saturated clothing immediately.

Fire prevent measures:

Store in a well-ventilated place. Keep cool.

Measures to prevent aerosol and dust generation:

Wipe for cleaning Do not use for injecting or spraying.

Environmental precautions:

Do not allow to enter into surface water or drains.

Advices on general occupational hygiene

Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air. Take precautionary measures against static discharge.

Packaging materials:

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Requirements for storage rooms and vessels:

Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs. Oxidising agent, strong.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

7.3. Specific end use(s)

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 5/11

FSG-Acetone

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³)
WEL (GB)	acetone CAS No.: 67-64-1 EC No.: 200-662-2	① 500 ppm (1,210 mg/m ³) ② 1,500 ppm (3,620 mg/m ³)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1,210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	200 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	2,420 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	186 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg	① DNEL Consumer ② Long-term - dermal, systemic effects
acetone CAS No.: 67-64-1 EC No.: 200-662-2	62 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	10.6 mg/L	① PNEC aquatic, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	1.06 mg/L	① PNEC aquatic, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	100 mg/L	① PNEC sewage treatment plant
acetone CAS No.: 67-64-1 EC No.: 200-662-2	30.4 mg/kg	① PNEC sediment, freshwater
acetone CAS No.: 67-64-1 EC No.: 200-662-2	3.04 mg/kg	① PNEC sediment, marine water
acetone CAS No.: 67-64-1 EC No.: 200-662-2	21 mg/L	① PNEC aquatic, intermittent release

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 6/11

FSG-Acetone

Substance name	PNEC Value	① PNEC type
acetone CAS No.: 67-64-1 EC No.: 200-662-2	29.5 mg/kg	① PNEC soil, freshwater

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Suitable eye protection: Eye glasses with side protection.

Skin protection:

Wear suitable gloves. Tested protective gloves must be worn Solvent.

Check leak tightness/impermeability prior to use.

Suitable material: Butyl caoutchouc (butyl rubber) Breakthrough time: ≥ 4 h, Thickness of the glove material: 0,5 mm, EN ISO 374.

Unsuitable material: NR (natural rubber, Natural latex), CR (polychloroprene, chloroprene rubber), PVC (polyvinyl chloride). The following gloves may be used: Ultranitrl 492, MAPA Professionnel & Nitril/ Neopren Microflex 93-260 (EN374(JKL), EN388 (2000); Kat.III; AQL 0,65).

Respiratory protection:

Respiratory protection necessary at: exceeding exposure limit values. In case of inadequate ventilation wear respiratory protection. Filtering device (full mask or mouthpiece) with filter: AX. EN 141.

Other protection measures:

Protective clothing.

8.2.3. Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: colourless

Odour: Acetone

Odour threshold: approx. 13 ppm

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	5 - 6	20 °C	① 395 g/l ② MSDS Distributor
Melting point	-94.7 °C		② MSDS Distributor
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	56.05 °C		② MSDS Distributor
Decomposition temperature	<i>not determined</i>		
Flash point	-17 °C		② MSDS Distributor
Evaporation rate	2		① Ether =1
Auto-ignition temperature	465 °C		② MSDS Distributor
Upper/lower flammability or explosive limits	2.5 - 14.3 Vol-%		① The formation of explosive vapor / air mixtures is possible. ② MSDS Distributor
Vapour pressure	240 hPa	20 °C	② MSDS Distributor
Vapour density	2.1	20 °C	② MSDS Distributor
Density	0.791 g/cm ³	20 °C	② MSDS Distributor
Relative density	<i>not determined</i>		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 7/11

FSG-Acetone

Parameter	Value	at °C	① Method ② Remark
Bulk density	<i>not determined</i>		
Water solubility	completely miscible		② MSDS Distributor
Partition coefficient: n-octanol/water	-0.24	20 °C	② MSDS Distributor
Dynamic viscosity	0.32 mPa* s	20 °C	② MSDS Distributor
Kinematic viscosity	<i>not determined</i>		
Oxidising liquids			① Not oxidising. ② MSDS Distributor

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Adverse physicochemical effects: Catches fire spontaneously if exposed to air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

May form explosive peroxides.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Thermal decomposition 235 °C.

10.5. Incompatible materials

Oxidising agent, strong Reducing agent, strong other halogenated solvents and solvent mixtures Alkali metals Ethanolamine Hydrogen peroxide.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO₂).

Further information

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

acetone CAS No.: 67-64-1 EC No.: 200-662-2
LD₅₀ oral: 5,800 mg/kg (Rat) Journal of Toxicology and Environmental Health. Vol. 15, Pg. 609, 1985.
LD₅₀ dermal: >7,426 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (vapour): 50.1 mg/L (Rat) Am Ind Hyg Assoc J 20: 364-369

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

not relevant

Additional information:

Symptoms/ delayed effects Headache Nausea Vomiting Dizziness Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

11.2. Information on other hazards

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 8/11

FSG-Acetone

SECTION 12: Ecological information

12.1. Toxicity

acetone CAS No.: 67-64-1 EC No.: 200-662-2

LC₅₀: 4,350 - 11,000 mg/L 4 d (fish, Pimephales promelas (fathead minnow)) OECD Guideline 203 (Fish, Acute Toxicity Test)

LC₅₀: 10 - 30,600 mg/L 2 d (crustaceans, Daphnia pulex (water flea)) Cowgill, U.M., and D.P. Milazzo 1991. The Sensitivity of Ceriodaphnia dubia and Daphnia magna to Seven Chemicals Utilizing the Three-Brood Test. Arch. Environ. Contam. Toxicol. 20(2):211-217; Canton, J.H., and D.M.M. Adema 1978. Reproducibility of Short-Term and Reproduction Toxicity Experiments with Daphnia magna and Comparison of the Sensitivity of Daphnia magna with Daphnia pulex and Daphnia cucullata in Short-Term Experiments. Hydrobiologia 59(2):135-140 (Used Reference 2018)

EC₅₀: 13,500 - 23,500 mg/L 2 d (crustaceans) Randall, T.L., and P.V. Knopp 1980. Detoxification of Specific Organic Substances by Wet Oxidation. J. Water Pollut. Control Fed. 52(8):2117-2130; Barera, Y., and W.J. Adams 1983. Resolving Some Practical Questions About Daphnia Acute Toxicity Tests. In: W.E. Bishop (Ed.), Aquatic Toxicology and Hazard Assessment, 6th Symposium, ASTM STP 802, Philadelphia, PA :509-518

EC₅₀: 7,200 - 7,200 mg/L 4 d (Algae/water plant, Microcystis aeruginosa) Slooff, W. 1982. A Comparative Study on the Short-Term Effects of 15 Chemicals on Fresh Water Organisms of Different Tropic Levels. Natl. Tech. Inf. Serv., Springfield, VA :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)

12.2. Persistence and degradability

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Biodegradation: Yes, rapidly

Biodegradation:

91% - Readily biodegradable (C9 - C11) , 89 % (exposure duration 28d) Readily biodegradable.

Additional information:

Hydrolysis

12.3. Bioaccumulative potential

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Log K_{ow}: -0.24

Bioconcentration factor (BCF): 3

Partition coefficient: n-octanol/water:

-0.24 at °C: 20; Remark: MSDS Distributor

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

Product is easily volatile.

12.5. Results of PBT and vPvB assessment

acetone CAS No.: 67-64-1 EC No.: 200-662-2

Results of PBT and vPvB assessment: —

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Biochemical oxygen demand 1900 mg/g (Test duration 5 d,
Chemical oxygen demand (COD) 2100 mg/g

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Do not mix with other wastes. Dispose of this material and its container to hazardous or special waste collection point. Delivery to an approved waste disposal company.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 9/11

FSG-Acetone

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

14 06 03 *	other solvents and solvent mixtures
------------	-------------------------------------

*: Evidence for disposal must be provided.

Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
------	-----------

Waste code packaging

15 01 05	composite packaging
----------	---------------------

Waste treatment options

Appropriate disposal / Product:

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Appropriate disposal / Package:

Contaminated packages must be completely emptied and can be re-used following proper cleaning. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

13.2. Additional information

Return to Distributor..

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1090	UN 1090	UN 1090	UN 1090
14.2. UN proper shipping name			
ACETONE (Acetone)	ACETONE (Acetone)	ACETONE	ACETONE
14.3. Transport hazard class(es)			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Limited quantity (LQ): 1L Excepted Quantities (EQ): - Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E) Remark: -	Limited quantity (LQ): 1L Excepted Quantities (EQ): - Classification code: F1 Remark: -	Limited quantity (LQ): 1 L Excepted Quantities (EQ): - EmS-No.: F-E; S-D Remark: -	Limited quantity (LQ): 1L Excepted Quantities (EQ): - Remark: -

14.7. Maritime transport in bulk according to IMO instruments

IMDG void.

Additional information:

-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 10/11

FSG-Acetone

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 100 weight-%

15.1.2. National regulations

[GB] National regulations

Other regulations, restrictions and prohibition regulations

Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)

Regulation 850/2004/EC on persistent organic pollutants (POP)

Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

For abbreviations and acronyms, see ECHA: Guidance on information requirements and chemical safety assessment, Chapter R.20 (list of terms and abbreviations).

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental hazard information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

16.6. Training advice

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 11/11

FSG-Acetone

16.7. Additional information

The information provided in this safety data sheet is correct to the best of our knowledge at the time of going to press. This information is intended to provide guidance for the safe handling, storage, processing, transport and disposal of the product mentioned in this safety data sheet. The information is not transferable to other products. If the product is mixed with other materials, mixed or processed, or subjected to processing, the data contained in this safety data sheet can not be transferred to the new material thus produced unless otherwise expressly stated otherwise.