

FSG Colour Touch-Up

Application

- For opaque dyeing of closed surfaces made of wood, plastic and metal.
- For fast, easy colouring of corners, edges and grooves.
- For painting guide grooves on foil laminated PVC window profiles and doors.
- For indoor and outdoor use.

Characteristics

- Acrylic-based pigmented topcoat.
- Fast drying
- High opacity
- Good adhesion to many lacquer, plastic and metal surfaces.
- Good lightfastness and weathering resistance (with corresponding layer thickness)

Instructions for Use

- Shake closed bottle - (mixing balls must be audible)
- Lacquer can be used as soon as the pigments have been mixed evenly with the lacquer
- Test the colour accuracy of FSG Colour Touch-Up after the paint is dry (about 2 min. after application).
Important: Immediately after use close – to prevent desiccation!

Technical Data and Shelf Life

Touch-dry:	approx. 1-2 min.
Film strength:	approx. 2-5 min. (values depend on room temperature)
Lightfastness:	good
Weathering resistance:	good
Shelf Life:	min. 2 years (in closed original container and at room temperature)

Safety Precautions and Suggestions

- Highly flammable liquid and vapour.
- Harmful if swallowed.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Avoid breathing dust / fume / gas / mist / vapours / spray.
- Do not eat, drink or smoke when using this product.
- IF SWALLOWED: Call a POISON CENTER / doctor / ... / if you feel unwell.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Call a POISON CENTER or doctor, if you feel unwell.

Extract from the legal texts. More details on the label and safety data sheet.

Storage and Disposal

- Do not allow to enter into surface water or drains.
- Dispose residues of the lacquer corresponding waste code 08 01 11 (Waste paint and varnish, which dispose of organic solvents or other dangerous substances).
- Return empty containers to manufacturer or emptied for material recycling options.
- For more information see safety data sheet or consult the appropriate local waste disposal expert.

Delivery form

- 3 ml
- 30 ml
- 250 ml
- 500 ml
- 1.000 ml

This information has been carefully checked, should not and cannot be legally binding and do not exempt you from own tests of the products supplied by us as to their suitability for the intended applications. Optionally, methods need to be adapted to the specific requirements in each case.