

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 1/19

FSG-Correction Lacquer (various colours)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

FSG-Correction Lacquer (various colours)

Article No.:

FE61001

UFI:

Y7XE-0561-E00M-9D8N

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Restoration Kit

Relevant identified uses:

Sector of uses [SU]

SU 6a: Manufacture of wood and wood products

Product Categories [PC]

PC 9: Coatings and paints, fillers, putties, thinners

Article categories [AC]

AC 11: Wood articles: furniture

* 1.3. Details of the supplier of the safety data sheet

Manufacturer:

FSG Schäfer GmbH

Boschstraße 14

48703 Stadthoorn

GERMANY

Telephone: +49 (0) 25 63 - 93 95 - 0

Telefax: +49 (0) 25 63 - 93 95 - 25

E-mail: verkauf@fsg-schaefer.de

Website: www.fsg-schaefer.de

E-mail (competent person): sdb@fsg-schaefer.de

Only for information: National Poisons Information Service (Birmingham Unit): 844 892 0111

* 1.4. Emergency telephone number

24h: Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department., Office FSG: +49 (0) 2563 93950. (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Germ cell mutagenicity (<i>Muta. 1B</i>)	H340: May cause genetic defects.	
Carcinogenicity (<i>Carc. 1B</i>)	H350: May cause cancer.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 2/19

FSG-Correction Lacquer (various colours)

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. (central nervous system)	
Hazardous to the aquatic environment (Aquatic Chronic 2)	H411: Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark



GHS08
Health hazard



GHS09
Environment

Signal word: Danger

Hazard statements for physical hazards	
H225	Highly flammable liquid and vapour.

Hazard statements for health hazards	
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure. (central nervous system)

Hazard statements for environmental hazards	
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information: none

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.

Precautionary statements Response	
P301 + P312	IF SWALLOWED: Call a POISON CENTER/doctor/First aider/ if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/First aider if you feel unwell.

Special rules for supplemental label elements for certain mixtures:

4,9 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).

3,8 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (inhalative).

2.3. Other hazards

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 3/19

FSG-Correction Lacquer (various colours)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 123-86-4 EC No.: 204-658-1 Index No.: 607-025-00-1 REACH No.: 01-2119485493-29-0007	n-butyl acetate Flam. Liq. 3 (H226), STOT SE 3 (H336) Warning EUH066	34 - < 60 weight-%
CAS No.: 108-10-1 EC No.: 203-550-1 Index No.: 606-004-00-4 REACH No.: 01-2119473980-30	4-methylpentan-2-one Acute Tox. 4 (H332), Carc. 2 (H351), Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066 Acute Toxicity Estimate ATE (inhalation, vapour): 11 mg/L	12 - < 25 weight-%
CAS No.: 64-17-5 EC No.: 200-578-6 Index No.: 603-002-00-5	ethanol Flam. Liq. 2 (H225) Danger	3 - ≤ 5.002936 weight-%
CAS No.: 108-65-6 EC No.: 203-603-9 Index No.: 607-195-00-7	2-methoxy-1-methylethyl acetate Flam. Liq. 3 (H226) Warning	2 - < 4 weight-%
EC No.: 927-241-2 Index No.: 649-330-00-2 REACH No.: 01-2119471843-32-0000	Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics Asp. Tox. 1 (H304), Carc. 1B (H350), Muta. 1B (H340), STOT RE 1 (H372) Danger	1 - < 3 weight-%
CAS No.: 13463-67-7 EC No.: 236-675-5 Index No.: 022-006-00-2 REACH No.: 01-2119489379-17-0000	titanium dioxide Carc. 2 (H351) Warning	0 - < 1 weight-%
CAS No.: 64742-95-6 EC No.: 918-668-5 REACH No.: 01-2119455851-35	Hydrocarbons, C9, aromatics Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336) Danger	0 - < 0.42 weight-%
CAS No.: 78-83-1 EC No.: 201-148-0 Index No.: 603-108-00-1 REACH No.: 01-2119484609-23	2-methylpropan-1-ol Eye Dam. 1 (H318), Flam. Liq. 3 (H226), STOT SE 3 (H335, H336), Skin Irrit. 2 (H315) Danger	0 - < 0.09 weight-%
CAS No.: 1330-20-7 EC No.: 215-535-7 Index No.: 601-022-00-9 REACH No.: 01-2119488216-32	xylene Acute Tox. 4 (H332, H312), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315) Warning	0 - < 0.05 weight-%
CAS No.: 70657-70-4 EC No.: 274-724-2 Index No.: 607-251-00-0	2-methoxypropyl acetate Flam. Liq. 3 (H226), Repr. 1B (H360D***), STOT SE 3 (H335) Danger	0 - < 0.002399 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 4/19

FSG-Correction Lacquer (various colours)

If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention if you feel unwell.

In case of skin contact:

If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap.

After eye contact:

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Rinse cautiously with water for several minutes.

Following ingestion:

Rinse mouth. Get medical advice/attention if you feel unwell. Let 1 glass of water be drunk in little sips (dilution effect).

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider.

* 4.2. Most important symptoms and effects, both acute and delayed

Serious eye damage/eye irritation, Dizziness, Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).
Fire extinguishers Fire class B.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable, Combustible.

Hazardous combustion products:

In case of fire may be liberated: Carbon dioxide, Carbon monoxide, Pyrolysis products, toxic, carbon black.

In case of fire: Gases/vapours, toxic.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Special danger of slipping by leaking/spilling product. Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Discharge into the environment must be avoided. Do not allow to enter into surface water or drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 5/19

FSG-Correction Lacquer (various colours)

6.3. Methods and material for containment and cleaning up

For containment:

Soak up inert absorbent and dispose as waste requiring special attention.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Clean with detergents. Avoid solvent cleaners. Water (with cleaning agent).

6.4. Reference to other sections

Safe handling: see section 7.

Personal protection equipment: see section 8.

Disposal: see section 13.

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

* 7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment). Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

Measures to prevent aerosol and dust generation:

Technical ventilation of workplace.

Environmental precautions:

Discharge into the environment must be avoided.

Advices on general occupational hygiene

Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Packaging materials:

Keep/Store only in original container.

Requirements for storage rooms and vessels:

Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on storage assembly:

Do not store together with: Strong acid, Base, alkaline materials, Oxidising agent, strong.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Protect from sunlight. Store in a well-ventilated place.

* 7.3. Specific end use(s)

Recommendation:

Keep out of the reach of children.

Industrial sector specific solutions:

Solvent-based varnishes/wood glazes, low in aromatics.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 6/19

FSG-Correction Lacquer (various colours)

GISCODE:

M-KH03

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU) from 20 Nov 2019	n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	① 50 ppm (241 mg/m ³) ② 150 ppm (723 mg/m ³)
IOELV (EU)	4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	① 20 ppm (83 mg/m ³) ② 50 ppm (208 mg/m ³)
WEL (GB)	4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	① 50 ppm (208 mg/m ³) ② 100 ppm (416 mg/m ³) ⑤ (may be absorbed through the skin)
WEL (GB)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,920 mg/m ³)
IOELV (EU)	2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (275 mg/m ³) ② 100 ppm (550 mg/m ³) ⑤ (may be absorbed through the skin)
WEL (GB)	2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	① 50 ppm (274 mg/m ³) ② 100 ppm (548 mg/m ³) ⑤ (may be absorbed through the skin)
WEL (GB)	titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	① 10 mg/m ³ ⑤ (inhalable fraction)
WEL (GB)	titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	① 4 mg/m ³ ⑤ (respirable fraction)
WEL (GB)	Hydrocarbons, C9, aromatics CAS No.: 64742-95-6 EC No.: 918-668-5	① 500 mg/m ³ ⑤ (Aromatics)
WEL (GB)	2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	① 50 ppm (154 mg/m ³) ② 75 ppm (231 mg/m ³)
IOELV (EU)	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (may be absorbed through the skin)
WEL (GB)	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	① 50 ppm (220 mg/m ³) ② 100 ppm (441 mg/m ³) ⑤ (may be absorbed through the skin)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 7/19

FSG-Correction Lacquer (various colours)

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
BMGV (GB)	4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	20 µmol/L	① 4-methylpentan - 2-one ② urine ③ end of exposure or end of shift
BMGV (GB) from 30 Nov 2022	xylene CAS No.: 1330-20-7 EC No.: 215-535-7	650 mmol/mol creatinine	① methyl hippuric acid ② urine ③ end of exposure or end of shift

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	48 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	102.34 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	859.7 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	480 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	600 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	7 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	11 mg/kg bw/ day	① DNEL worker ② Acute - dermal, systemic effects
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	83 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	14.7 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	208 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	11.8 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	4.2 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	4.2 mg/m ³	① DNEL worker ② Long-term - oral, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 8/19

FSG-Correction Lacquer (various colours)

Substance name	DNEL value	① DNEL type ② Exposure route
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	114 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	1,900 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	343 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	206 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/ day	① DNEL worker ② Acute - oral, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	275 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	33 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	33 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	500 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	796 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	320 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	36 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	185 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	77 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	46 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	300 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 9/19

FSG-Correction Lacquer (various colours)

Substance name	DNEL value	① DNEL type ② Exposure route
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	46 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	10 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	700 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 64742-95-6 EC No.: 918-668-5	150 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 64742-95-6 EC No.: 918-668-5	32 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 64742-95-6 EC No.: 918-668-5	25 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 64742-95-6 EC No.: 918-668-5	11 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C9, aromatics CAS No.: 64742-95-6 EC No.: 918-668-5	11 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	310 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	55 mg/m ³	① DNEL Consumer ② Long-term - inhalation, local effects

Substance name	PNEC Value	① PNEC type
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	0.18 mg/L	① PNEC aquatic, freshwater
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	0.018 mg/L	① PNEC aquatic, marine water
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	35.6 mg/L	① PNEC sewage treatment plant
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	0.981 mg/L	① PNEC sediment, freshwater
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	0.0981 mg/L	① PNEC sediment, marine water
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	0.36 mg/L	① PNEC aquatic, intermittent release
n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1	0.0903 mg/L	① PNEC soil, freshwater
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	600 µg/L	① PNEC aquatic, freshwater

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 10/19

FSG-Correction Lacquer (various colours)

Substance name	PNEC Value	① PNEC type
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	60 µg/L	① PNEC aquatic, marine water
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	27.5 mg/L	① PNEC sewage treatment plant
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	8.27 mg/kg	① PNEC sediment, freshwater
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	0.83 mg/kg	① PNEC sediment, marine water
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	1.3 mg/kg	① PNEC soil
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1	1.5 mg/L	① PNEC aquatic, intermittent release
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.96 mg/L	① PNEC aquatic, freshwater
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.76 mg/L	① PNEC aquatic, marine water
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	580 mg/L	① PNEC sewage treatment plant
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	3.6 mg/kg	① PNEC sediment, freshwater
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.63 mg/kg	① PNEC soil, freshwater
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	635 µg/L	① PNEC aquatic, marine water
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	63.5 µg/L	① PNEC aquatic, marine water
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	100 mg/L	① PNEC sewage treatment plant
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	3.29 mg/kg	① PNEC sediment, freshwater
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	0.329 mg/kg	① PNEC sediment, marine water
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	0.29 mg/kg	① PNEC soil
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9	6.35 mg/L	① PNEC aquatic, intermittent release
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	0.127 mg/L	① PNEC aquatic, freshwater
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	1 mg/L	① PNEC aquatic, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 11/19

FSG-Correction Lacquer (various colours)

Substance name	PNEC Value	① PNEC type
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/L	① PNEC sewage treatment plant
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	1,000 mg/kg	① PNEC sediment, freshwater
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/kg	① PNEC sediment, marine water
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	1,667 mg/kg	① PNEC secondary poisoning
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	0.61 mg/L	① PNEC aquatic, intermittent release
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5	100 mg/kg	① PNEC soil, freshwater
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	400 µg/L	① PNEC aquatic, freshwater
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	40 µg/L	① PNEC aquatic, marine water
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	10 mg/L	① PNEC sewage treatment plant
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	1.56 mg/kg bw/day	① PNEC sediment, freshwater
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	156 mg/kg bw/ day	① PNEC sediment, marine water
2-methylpropan-1-ol CAS No.: 78-83-1 EC No.: 201-148-0	11 mg/L	① PNEC aquatic, intermittent release

* 8.2. Exposure controls

8.2.1. Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. generation/formation of aerosols: Technical ventilation of workplace.

8.2.2. Personal protection equipment



Eye/face protection:

In normal use (no eye contact): No goggles required. Eye glasses with side protection. EN 166.

Skin protection:

In full contact: Suitable material: Butyl caoutchouc (butyl rubber), Thickness of the glove material >0,7 mm, Breakthrough time: >480 min.

In splash contact: Suitable material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber) Thickness of the glove material >0,4 mm, Breakthrough time: >120 min.

In normal use (no skin contact): No gloves required.

Tested protective gloves must be worn EN ISO 374.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Breakthrough times and swelling properties of the material must be taken into consideration.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 12/19

FSG-Correction Lacquer (various colours)

Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Thermal hazards:

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Other protection measures:

Wear suitable protective clothing.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: by respective labeling.

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		
Melting point	<i>not determined</i>		
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	114 - 128 °C		
Decomposition temperature	<i>not determined</i>		
Flash point	14 °C		
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	<i>not determined</i>		
Upper/lower flammability or explosive limits	<i>not determined</i>		
Vapour pressure	<i>not determined</i>		
Vapour density	<i>not determined</i>		
Density	0.9 g/cm ³	20 °C	
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	partially miscible		
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	<i>not determined</i>		
Kinematic viscosity	<i>not determined</i>		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions /Exothermic reaction with: Strong acid, Base, Oxidising agent, strong.

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 13/19

FSG-Correction Lacquer (various colours)

10.5. Incompatible materials

Oxidising agent.

10.6. Hazardous decomposition products

In case of fire may be liberated: Flammable solvent vapor mixtures are possible.

Gases/vapours, toxic.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1
LD₅₀ oral: 10,760 mg/kg (Ratte) OECD Prüfrichtlinie 423
LD₅₀ dermal: >14,112 mg/kg (Rabbit) OECD Prüfrichtlinie 402
LC₅₀ Acute inhalation toxicity (dust/mist): 23.4 mg/L 4 h (Rat) OECD Prüfrichtlinie 403
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1
ATE (inhalation, vapour)¹: 11 mg/L
LD₅₀ oral: >2,000 - ≤5,000 mg/kg (Rat) MSDS Distributor
LD₅₀ dermal: >5,000 mg/kg (Rabbit) MSDS Distributor
LC₅₀ Acute inhalation toxicity (vapour): >10 - ≤20 mg/L 4 h (Rat)
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
LD₅₀ oral: 8,530 mg/kg (Ratte) Dow Chemical Company Reports. Vol. MSD-1582
LD₅₀ dermal: >5,000 mg/kg (Kaninchen) Dow Chemical Company Reports. Vol. MSD-1582
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2
LD₅₀ oral: >15,000 mg/kg (Rat) MSDS Distributor
LD₅₀ dermal: >5,000 mg/kg (Rabbit) MSDS Distributor
LC₅₀ Acute inhalation toxicity (dust/mist): >6.1 mg/L 4 h (Rat) MSDS Distributor
titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5
LD₅₀ oral: >2,000 - 25,000 mg/kg (Rat) OECD 425
LD₅₀ dermal: >5,000 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (dust/mist): 3.43 - 6.82 mg/L 4 h (Rat) ECHA
xylene CAS No.: 1330-20-7 EC No.: 215-535-7
LD₅₀ oral: 4,300 mg/kg (Rat) AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956.
LD₅₀ dermal: >1,700 mg/kg (Rabbit) Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974.
LC₅₀ Acute inhalation toxicity (dust/mist): 21.7 mg/L 4 h (Rat) Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974.

¹: Acute Toxicity Estimate. Harmonised (legal) classification.

Acute oral toxicity:

Harmful if swallowed.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

May cause genetic defects.

Carcinogenicity:

May cause cancer.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 14/19

FSG-Correction Lacquer (various colours)

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1
LC ₅₀ : 18 mg/L 4 d (fish, Pimephales promelas) OECD Prüfrichtlinie 203
EC ₅₀ : 32 - 44 mg/L 2 d (crustaceans, Daphnia magna)
EC ₅₀ : 246 - 647.7 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) Wachstumshemmung
NOEC: 105 - 196 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) Wachstumshemmung
NOEC: 23.2 mg/L 21 d (crustaceans)
IC ₅₀ : 356 mg/L 2 d (Tetrahymena)
4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1
LC ₅₀ : >100 mg/L (fish) MSDS Distributor
LC ₅₀ : >100 mg/L (crustaceans) MSDS Distributor
LC ₅₀ : ≤100 mg/L (Algae/water plant) MSDS Distributor
EC ₅₀ : >100 mg/L (fish) MSDS Distributor
EC ₅₀ : >100 mg/L (crustaceans) MSDS Distributor
EC ₅₀ : ≤100 mg/L (Algae/water plant) MSDS Distributor
IC ₅₀ : >100 mg/L (fish) MSDS Distributor
IC ₅₀ : >100 mg/L (crustaceans) MSDS Distributor
IC ₅₀ : ≤100 mg/L (Algae/water plant) MSDS Distributor
2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9
LC ₅₀ : 100 - 180 mg/L 4 d (fish)
EC ₅₀ : 500 mg/L 2 d (crustaceans)
NOEC: 100 mg/L 4 d (fish)
NOEC: 63.5 mg/L 12 d (fish)
NOEC: 100 mg/L 21 d (crustaceans)
NOEC: 1,000 mg/L 4 d (Algae/water plant)
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2
LC ₅₀ : 10 - ≤100 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) MSDS Distributor
LC ₅₀ : 10 - ≤100 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) MSDS Distributor
LC ₅₀ : >100 mg/L (Algae/water plant) MSDS Distributor
LC ₅₀ : >1,000 mg/L (Mikroorganismen) MSDS Distributor
LC ₅₀ : >10 - <30 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
EC ₅₀ : >1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) EL 50 SDB BR
EC ₅₀ : >22 - <46 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) EL 50 SDB BR
NOEC: <1 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) NOELR SDB BR

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 15/19

FSG-Correction Lacquer (various colours)

titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5

LC₅₀: >0.87 - 1.1 mg/L 4 d (fish, Pimephales promelas) ECHA

LC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna) ECHA

EC₅₀: 100 mg/L 3 d (Algae/water plant, Pseudokirchnerella subcapitata) ECHA

NOEC: ≥100 mg/L -∞ h (crustaceans, Hyalella azteca) ECHA

NOEC: 0.87 - 1.1 mg/L 12 d (fish) ECHA

NOEC: 0.004 - 0.08 mg/L 28 d (fish) ECHA

NOEC: 100 mg/L 3 d (Algae/water plant) ECHA

xylene CAS No.: 1330-20-7 EC No.: 215-535-7

LC₅₀: 3.3 - 780 mg/L 4 d (fish) Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212

LC₅₀: 8.5 - 8.5 mg/L 2 d (crustaceans)

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1

Biodegradation: Yes, rapidly

Remark: 83 % (aerob; Expositionsdauer: 28 d)(OECD Prüfrichtlinie 301D)

4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1

Biodegradation: Yes, rapidly

2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9

Biodegradation: Yes, rapidly

Remark: in Water

Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2

Biodegradation: Yes, rapidly

Remark: Bioakkumulation potentiell möglich, Schädlich für Fische.

titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5

Biodegradation: Yes, slowly

Remark: Bei diesem Pigment handelt es sich um einen anorganischen Stoff. Aufgrund seiner sehr geringen Wasserlöslichkeit und seines interten Charakters wird der Stoff als nicht bioverfügbar für Sediment und terrestrische Organismen betrachtet.

12.3. Bioaccumulative potential

n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1

Log K_{ow}: 2.3

4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1

Log K_{ow}: 1.31

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

n-butyl acetate CAS No.: 123-86-4 EC No.: 204-658-1

Results of PBT and vPvB assessment: —

4-methylpentan-2-one CAS No.: 108-10-1 EC No.: 203-550-1

Results of PBT and vPvB assessment: —

2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 EC No.: 203-603-9

Results of PBT and vPvB assessment: —

Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2

Results of PBT and vPvB assessment: —

titanium dioxide CAS No.: 13463-67-7 EC No.: 236-675-5

Results of PBT and vPvB assessment: —

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 16/19

FSG-Correction Lacquer (various colours)

xylylene CAS No.: 1330-20-7 EC No.: 215-535-7

Results of PBT and vPvB assessment: —

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

08 01 11 * Waste paint and varnish containing organic solvents or other dangerous substances

*: Evidence for disposal must be provided.

Waste code packaging

15 01 05 composite packaging

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Completely emptied packages can be recycled.





Other disposal recommendations:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

* 13.2. Additional information

Return to Distributor..

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 3363	UN 3363	UN 3363	UN 3363
14.2. UN proper shipping name			
DANGEROUS GOODS IN MACHINERY or DANGEROUS GOODS IN APPARATUS (n-Butyl acetate)	DANGEROUS GOODS IN MACHINERY or DANGEROUS GOODS IN APPARATUS (n-Butyl acetate)	DANGEROUS GOODS IN MACHINERY or DANGEROUS GOODS IN APPARATUS (n-Butyl acetate)	DANGEROUS GOODS IN MACHINERY or DANGEROUS GOODS IN APPARATUS (n-Butyl acetate)
14.3. Transport hazard class(es)			
 9	 9	 9	 9
14.4. Packing group			
		-	
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Limited quantity (LQ): SP301 Classification code: M11	Classification code: M11 Remark: -	Limited quantity (LQ): SP301 Remark: Stowage Category A	Limited quantity (LQ): SP301

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 17/19

FSG-Correction Lacquer (various colours)

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
Remark: -			

- * **14.7. Maritime transport in bulk according to IMO instruments**
not determined.

Additional information:

-

SECTION 15: Regulatory information

- * **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

15.1.1. EU legislation

Restrictions on use:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented. Observe employment restrictions for women of child-bearing age. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b
- E2 Hazardous to the Aquatic Environment in Category Chronic 2

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 90.5 weight-%

15.1.2. National regulations

[GB] National regulations

Other regulations, restrictions and prohibition regulations

Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)

Regulation 850/2004/EC on persistent organic pollutants (POP)

Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

- * **16.1. Indication of changes**

1.3.	Details of the supplier of the safety data sheet
1.4.	Emergency telephone number
4.2.	Most important symptoms and effects, both acute and delayed
7.1.	Precautions for safe handling
7.3.	Specific end use(s)
8.1.	Control parameters
8.2.	Exposure controls
9.1.	Information on basic physical and chemical properties
13.2.	Additional information
14.7.	Maritime transport in bulk according to IMO instruments
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes
16.2.	Abbreviations and acronyms

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 18/19

FSG-Correction Lacquer (various colours)

* 16.2. Abbreviations and acronyms

AC	Article Category
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM	American Society for Testing and Materials
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
DIN	German Institute for Standardization / German Industrial Standard
DNEL	derived no-effect level
EC ₅₀	Effective Concentration 50%
ECHA	European Chemicals Agency
EN	European Standard
ES	Exposure scenario
EWC	European Waste Catalogue
IC ₅₀	Inhibition Concentration 50 %
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
KG	body weight
LC ₅₀	Lethal (fatal) Concentration 50%
LD ₅₀	Lethal (fatal) Dose 50%
MAK	Maximum concentration in the workplace air (CH)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety & Health
NOEC	No Observed Effect Concentration
OECD	Organisation for Economic Cooperation and Development
OEL	Threshold Limit Value
OSHA	Occupational Safety & Health Administration
PBT	persistent and bioaccumulative and toxic
PC	Product category
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation and Authorization of Chemicals
RID	Dangerous goods regulations for transport by rail
STP	sewage treatment plant
SU	use category
TRGS	Technische Regeln für Gefahrstoffe
UN	United Nations
VOC	Volatile organic compounds
ZNS	central nervous system

For abbreviations and acronyms, see ECHA: Guidance on information requirements and chemical safety assessment, Chapter R.20 (list of terms and abbreviations).

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Acute toxicity (oral) (<i>Acute Tox. 4</i>)	H302: Harmful if swallowed.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	
Germ cell mutagenicity (<i>Muta. 1B</i>)	H340: May cause genetic defects.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 30 May 2023

Print date: 2 Jun 2023

Version: 0.2

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 19/19

FSG-Correction Lacquer (various colours)

Hazard classes and hazard categories	Hazard statements	Classification procedure
Carcinogenicity (<i>Carc. 1B</i>)	H350: May cause cancer.	
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure. (central nervous system)	
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version.