

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 1/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Article No.:

TR28000

UFI:

GXHG-022D-N00Y-HJQJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Antiadhesive-Agent

Relevant identified uses:

Sector of uses [SU]

SU 6a: Manufacture of wood and wood products

Product Categories [PC]

PC 24: Lubricants, greases, release products

Article categories [AC]

AC 11: Wood articles

1.3. Details of the supplier of the safety data sheet

Manufacturer:

FSG Schäfer GmbH

Boschstraße 14

48703 Stadthoorn

GERMANY

Telephone: +49 (0) 25 63 - 93 95 - 0

Telefax: +49 (0) 25 63 - 93 95 - 25

E-mail: verkauf@fsg-schaefer.de

Website: www.fsg-schaefer.de

E-mail (competent person): sdb@fsg-schaefer.de

Only for information: National Poisons Information Service (Birmingham Unit): 844 892 0111

1.4. Emergency telephone number

24h: Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department., Office FSG: +49 (0) 2563 93950. (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Germ cell mutagenicity (<i>Muta. 1B</i>)	H340: May cause genetic defects.	
Carcinogenicity (<i>Carc. 1B</i>)	H350: May cause cancer.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 2/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure. (central nervous system)	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark



GHS08
Health hazard

Signal word: Danger

Hazard statements for physical hazards	
H225	Highly flammable liquid and vapour.

Hazard statements for health hazards	
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure. (central nervous system)

Supplemental hazard information	
EUH208	Contains N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline. May produce an allergic reaction.

Precautionary statements Prevention	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/Personal protection.

Precautionary statements Response	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/First aider.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements Disposal	
P501	Dispose of contents/container to Disposal methods.

Special rules for supplemental label elements for certain mixtures:

5,5 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (oral).

70,4 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).

26,4 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (inhalative).

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Mixture of following listed substances with nonhazardous additions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 3/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64-17-5 EC No.: 200-578-6 Index No.: 603-002-00-5	ethanol Flam. Liq. 2 (H225) Danger	38 - < 80 weight-%
CAS No.: 67-63-0 EC No.: 200-661-7 Index No.: 603-117-00-0 REACH No.: 01-2119457558-25	propan-2-ol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger	7 - ≤ 14 weight-%
EC No.: 927-241-2 Index No.: 649-330-00-2 REACH No.: 01-2119471843-32-0000	Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics Asp. Tox. 1 (H304), Carc. 1B (H350), Muta. 1B (H340), STOT RE 1 (H372) Danger	4 - ≤ 9 weight-%
EC No.: 927-632-8 REACH No.: 01-2119457736-27-0000	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1 (H304) Danger	3 - < 6 weight-%
CAS No.: 78-93-3 EC No.: 201-159-0 Index No.: 606-002-00-3	butanone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	1 - < 2.03 weight-%
EC No.: 919-284-0 REACH No.: 01-2119463588-24-0000	Hydrocarbons, C10, Aromatics, >1% Naphtalene Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Carc. 2 (H351), STOT SE 3 (H336) Danger	0 - < 1.38 weight-%
CAS No.: 34432-92-3 EC No.: 252-021-1	N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazanylaniline Acute Tox. 4 (H302), Aquatic Chronic 4 (H413), STOT RE 2 (H373), Skin Sens. 1 (H317) Warning	0 - < 0.38 weight-%
EC No.: 926-273-4 REACH No.: 01-2119451151-53-0000	Hydrocarbons, C10 - C13, Aromatics, >1% Naphtalene Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Carc. 2 (H351) Danger	0 - < 0.03 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/attention if you feel unwell.

In case of skin contact:

Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. After contact with skin, wash immediately with plenty of water and soap.

After eye contact:

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Rinse cautiously with water for several minutes.

Following ingestion:

Rinse mouth. Get medical advice/attention if you feel unwell. Observe risk of aspiration if vomiting occurs. Let 1 glass of water be drunk in little sips (dilution effect). Do NOT induce vomiting. Get immediate medical advice/attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 4/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed

Pneumonia, Pulmonary oedema, Serious eye damage/eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).
Fire extinguishers Fire class B.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Highly flammable, Combustible.

Hazardous combustion products:

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂), Pyrolysis products, toxic, carbon black.

In case of fire: Gases/vapours, toxic.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Special danger of slipping by leaking/spilling product. Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Discharge into the environment must be avoided. Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Soak up inert absorbent and dispose as waste requiring special attention.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Clean with detergents. Avoid solvent cleaners. Water (with cleaning agent).

6.4. Reference to other sections

Safe handling: see section 7.

Personal protection equipment: see section 8.

Disposal: see section 13.

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 5/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Repeated exposure may cause skin dryness or cracking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Highly flammable, Take precautionary measures against static discharge. Keep away from sources of ignition - No smoking.

Environmental precautions:

Discharge into the environment must be avoided.

Advices on general occupational hygiene

Wash hands before breaks and after work. After cleaning apply high-fat content skin care cream. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Packaging materials:

Material, solvent-resistant, Keep/Store only in original container.

Requirements for storage rooms and vessels:

Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on storage assembly:

Keep away from combustible material. Do not store together with:
Combustible substances of acute toxicity, category 1 and 2 / very toxic substances,
Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances,
Combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects,
Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Protect from sunlight. Store in a well-ventilated place.

7.3. Specific end use(s)

Recommendation:

Lubricants, greases, release products,

Industrial sector specific solutions:

Anti-corrosive paints, containing solvents, aromatics removed

GISCODE:

BS40

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 6/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IE	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm
WEL (GB)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,920 mg/m ³)
IE	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 200 ppm ② 400 ppm ⑤ (may be absorbed through the skin) Sk
WEL (GB)	propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	① 400 ppm (999 mg/m ³) ② 500 ppm (1,250 mg/m ³)
IE	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (may be absorbed through the skin) Sk, IOELV
IOELV (EU)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
WEL (GB)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (899 mg/m ³)
WEL (GB)	Hydrocarbons, C10, Aromatics, >1% Naphtalene EC No.: 919-284-0	① 500 mg/m ³ ⑤ (Aromatics)

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	114 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	1,900 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	343 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	206 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 7/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Substance name	DNEL value	① DNEL type ② Exposure route
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/day	① DNEL worker ② Long-term - oral, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/day	① DNEL worker ② Acute - oral, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	500 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	89 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	319 mg/kg	① DNEL Consumer ② Long-term - dermal, systemic effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	888 mg/kg	① DNEL worker ② Long-term - dermal, local effects
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	26 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	185 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	77 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	46 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	300 mg/kg bw/day	① DNEL worker ② Long-term - oral, systemic effects
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2	46 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	600 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	106 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	1,161 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	412 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	31 mg/kg bw/day	① DNEL worker ② Long-term - oral, systemic effects
Hydrocarbons, C10, Aromatics, >1% Naphtalene EC No.: 919-284-0	151 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 8/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Substance name	DNEL value	① DNEL type ② Exposure route
Hydrocarbons, C10, Aromatics, >1% Naphthalene EC No.: 919-284-0	32 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C10, Aromatics, >1% Naphthalene EC No.: 919-284-0	12.5 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C10, Aromatics, >1% Naphthalene EC No.: 919-284-0	7.5 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C10, Aromatics, >1% Naphthalene EC No.: 919-284-0	7.5 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
1,4-bis({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione; 1,4-bis[(2-ethylhexyl)amino]-9,10-dihydroanthracene-9,10-dione; 1-[(2-ethylhexyl)amino]-4-({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione CAS No.: 90170-70-0 EC No.: 290-505-4	1.1 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
1,4-bis({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione; 1,4-bis[(2-ethylhexyl)amino]-9,10-dihydroanthracene-9,10-dione; 1-[(2-ethylhexyl)amino]-4-({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione CAS No.: 90170-70-0 EC No.: 290-505-4	0.193 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
1,4-bis({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione; 1,4-bis[(2-ethylhexyl)amino]-9,10-dihydroanthracene-9,10-dione; 1-[(2-ethylhexyl)amino]-4-({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione CAS No.: 90170-70-0 EC No.: 290-505-4	0.156 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
1,4-bis({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione; 1,4-bis[(2-ethylhexyl)amino]-9,10-dihydroanthracene-9,10-dione; 1-[(2-ethylhexyl)amino]-4-({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione CAS No.: 90170-70-0 EC No.: 290-505-4	0.0556 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 9/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Substance name	DNEL value	① DNEL type ② Exposure route
1,4-bis({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione; 1,4-bis[(2-ethylhexyl)amino]-9,10-dihydroanthracene-9,10-dione; 1-[(2-ethylhexyl)amino]-4-({3-[(2-ethylhexyl)oxy]propyl}amino)-9,10-dihydroanthracene-9,10-dione CAS No.: 90170-70-0 EC No.: 290-505-4	0.0556 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.353 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.087 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.1 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.05 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.05 mg/kg bw/day	① DNEL worker ② Long-term - oral, systemic effects
Hydrocarbons, C10 - C13, Aromatics, >1% Naphtalene EC No.: 926-273-4	1.51 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Hydrocarbons, C10 - C13, Aromatics, >1% Naphtalene EC No.: 926-273-4	32 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Hydrocarbons, C10 - C13, Aromatics, >1% Naphtalene EC No.: 926-273-4	12.5 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Hydrocarbons, C10 - C13, Aromatics, >1% Naphtalene EC No.: 926-273-4	7.5 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Hydrocarbons, C10 - C13, Aromatics, >1% Naphtalene EC No.: 926-273-4	7.5 mg/kg	① DNEL Consumer ② Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.96 mg/L	① PNEC aquatic, freshwater
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.76 mg/L	① PNEC aquatic, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 10/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Substance name	PNEC Value	① PNEC type
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	580 mg/L	① PNEC sewage treatment plant
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	3.6 mg/kg	① PNEC sediment, freshwater
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.63 mg/kg	① PNEC soil, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	140.9 mg/L	① PNEC aquatic, marine water
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	2,251 mg/L	① PNEC sewage treatment plant
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	552 mg/kg	① PNEC sediment, freshwater
propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7	28 mg/kg	① PNEC soil, freshwater
butanone CAS No.: 78-93-3 EC No.: 201-159-0	55.8 mg/L	① PNEC aquatic, freshwater
butanone CAS No.: 78-93-3 EC No.: 201-159-0	55.8 mg/L	① PNEC aquatic, marine water
butanone CAS No.: 78-93-3 EC No.: 201-159-0	709 mg/L	① PNEC sewage treatment plant
butanone CAS No.: 78-93-3 EC No.: 201-159-0	284.74 mg/kg	① PNEC sediment, freshwater
butanone CAS No.: 78-93-3 EC No.: 201-159-0	284.7 mg/kg	① PNEC sediment, marine water
butanone CAS No.: 78-93-3 EC No.: 201-159-0	1 g/kg	① PNEC secondary poisoning
butanone CAS No.: 78-93-3 EC No.: 201-159-0	55.8 mg/L	① PNEC aquatic, intermittent release
butanone CAS No.: 78-93-3 EC No.: 201-159-0	22.5 mg/kg	① PNEC soil, freshwater
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.003 mg/L	① PNEC aquatic, freshwater
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.003 mg/L	① PNEC aquatic, marine water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 11/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Substance name	PNEC Value	① PNEC type
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	9.6914 mg/kg	① PNEC sediment, freshwater
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	0.9691 mg/kg	① PNEC sediment, marine water
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1	2.6789 mg/kg	① PNEC soil, freshwater

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. generation/formation of aerosols: Technical ventilation of workplace.

8.2.2. Personal protection equipment



Eye/face protection:

Eye glasses with side protection EN 166.

Skin protection:

Tested protective gloves must be worn. EN ISO 374.

In full contact: Suitable material: Butyl caoutchouc (butyl rubber), Thickness of the glove material >0,7 mm. Breakthrough time: >480 min.

In splash contact: Suitable material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber), Thickness of the glove material >0,4 mm. Breakthrough time: >120 min.

The following gloves may be used: Ultranitriil 492, MAPA Professionnel & Nitril/Neopren Microflex 93-260 (EN374(JKL), EN388 (2000); Kat.III; AQL 0,65).

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device with filter or ventilator filtering device of type: AX.

Thermal hazards:

Risk of explosion if heated under confinement.

Other protection measures:

Wear suitable protective clothing.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: yellow

Odour: Ethanol

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 12/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	7		② pH neutral
Melting point	<i>not determined</i>		
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	78 - 137 °C		
Decomposition temperature	<i>not determined</i>		
Flash point	12 °C		
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	<i>not determined</i>		
Upper/lower flammability or explosive limits	<i>not determined</i>		
Vapour pressure	<i>not determined</i>		
Vapour density	<i>not determined</i>		
Density	<i>not determined</i>		
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	partially miscible		
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	<i>not determined</i>		
Kinematic viscosity	0.87 mm ² /s	40 °C	

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Combustible substance, Highly flammable liquid and vapour.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions/Exothermic reaction with: Acid, Light metals, (Formation of: Hydrogen).

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5. Incompatible materials

Oxidising agent.

10.6. Hazardous decomposition products

In case of warming: Flammable solvent vapor mixtures are possible.
Gases/vapours, toxic.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LD₅₀ oral: 5,050 mg/kg (Rat)
LD₅₀ dermal: 12,800 mg/m ³ (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): >25,000 mg/kg 6 h (Rat)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 13/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2
LD₅₀ oral: >15,000 mg/kg (Rat) MSDS Distributor
LD₅₀ dermal: >5,000 mg/kg (Rabbit) MSDS Distributor
LC₅₀ Acute inhalation toxicity (dust/mist): >6.1 mg/L 4 h (Rat) MSDS Distributor
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 927-632-8
LD₅₀ oral: >5,000 mg/kg (Rat) Under the test conditions, MRD-83-207 is not classified according to the criteria of Annex VI to the Directive 67/548/EEC and CLP Regulation 1272/2008.
LD₅₀ dermal: >1,082 mg/kg (Rat) MRD83-207 is not classified according to the criteria of Annex VI to the Directive 67/548/EEC and CLP Regulation 1272/2008.
LC₅₀ Acute inhalation toxicity (gas): ≥5.266 - 5.991 mg/L 4 h (Rat) Under the conditions of the test, C14-C16 n-Paraffins are not classified according to the criteria of Annex VI to the Directive 67/548/EEC and EU GHS.
butanone CAS No.: 78-93-3 EC No.: 201-159-0
LD₅₀ oral: 2,740 mg/kg (Rat) Toxicology and Applied Pharmacology. Vol. 19, Pg. 699, 1971.
LD₅₀ dermal: 6,480 mg/kg (Rabbit) Shell Chemical Company. Vol. MSDS-5390-4,
Hydrocarbons, C10, Aromatics, >1% Naphtalene EC No.: 919-284-0
LD₅₀ oral: 5,210 - 10,650 mg/kg (Rat) combined LD 50
LD₅₀ dermal: >2,000 mg/kg (Rat)
LC₅₀ Acute inhalation toxicity (gas): >4,688 mg/m ³ 4 h (Rat)
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1
LD₅₀ oral: ≥300 - ≤2,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Contains N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline. May produce an allergic reaction.

Germ cell mutagenicity:

May cause genetic defects.

Carcinogenicity:

May cause cancer.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Additional information:

No data available

11.2. Information on other hazards

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 14/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

SECTION 12: Ecological information

12.1. Toxicity

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
LC₅₀: 9,640 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
LC₅₀: 9,714 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
NOEC: 250 mg/L 4 d (Algae/water plant, Tetrahymena thermophila)
NOEC: 754 mg/L 2 d (Algae/water plant)
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2
LC₅₀: 10 - ≤100 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) MSDS Distributor
LC₅₀: 10 - ≤100 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) MSDS Distributor
LC₅₀: >100 mg/L (Algae/water plant) MSDS Distributor
LC₅₀: >1,000 mg/L (Mikroorganismen) MSDS Distributor
LC₅₀: >10 - <30 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
EC₅₀: >1,000 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) EL 50 SDB BR
EC₅₀: >22 - <46 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) EL 50 SDB BR
NOEC: <1 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata) NOELR SDB BR
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 927-632-8
LC₅₀: 1,000 mg/L 4 d (crustaceans, Corophium volutator) mg/kg Sediment DW
LC₅₀: >1,082 - 87,556 mg/L 4 d (fish, Scophthalmus maximus) LL50/LC ₅₀ see GUIDANCE DOCUMENT ON AQUATIC TOXICITY TESTING OF DIFFICULT SUBSTANCES AND MIXTURES"
EC₅₀: 1,000 - 10,000 mg/L 4 d (Algae/water plant) LL50/LC ₅₀ see GUIDANCE DOCUMENT ON AQUATIC TOXICITY TESTING OF DIFFICULT SUBSTANCES AND MIXTURES"
butanone CAS No.: 78-93-3 EC No.: 201-159-0
LC₅₀: 3,220 - 3,220 mg/L 4 d (fish, Pimephales promelas) Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984 Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior, Superior, WI :414
EC₅₀: 5,090 - 5,090 mg/L 2 d (crustaceans) Randall, T.L., and P.V. Knopp 1980. Detoxification of Specific Organic Substances by Wet Oxidation. J.Water Pollut.Control Fed. 52(8):2117-2130
EC₅₀: 2,029 mg/L 4 d (Algae/water plant) ECHA
NOEC: 68 mg/L 2 d (crustaceans) ECHA
Hydrocarbons, C10, Aromatics, >1% Naphtalene EC No.: 919-284-0
LC₅₀: ≥2 - ≤5 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) LL50 values, Water accommodated fractions of hydrocarbons, C10, aromatics, >1% naphthalene, produced a 96-hour LL50 value between 2 and 5 mg/L with rainbow trout, Oncorhynchus mykiss. GUIDANCE DOCUMENT ON AQUATIC TOXICITY TESTING OF DIFFICULT SUBSTANCES AND MIXTURES"
EC₅₀: 0.55 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) Measured value for the 48-hour EC ₅₀ = 0.55mg/l with 95% CI of 0.47 to 0.65mg/l.
EC₅₀: 0.82 mg/L 1 d (crustaceans, Daphnia magna (Big water flea)) Measured value for the 48-hour EC ₅₀ = 0.55mg/l with 95% CI of 0.47 to 0.65mg/l.
EC₅₀: >1 - <3 mg/L 3 d (Algae/water plant, Pseudokirchnerella subcapitata) EL 50 value GUIDANCE DOCUMENT ON AQUATIC TOXICITY TESTING OF DIFFICULT SUBSTANCES AND MIXTURES"
NOEC: 0.487 mg/L -∞ h (crustaceans, Oncorhynchus mykiss (Rainbow trout)) NOELR value
NOEC: 0.851 mg/L -∞ h (crustaceans, Daphnia magna (Big water flea)) NOELR value
NOEC: 1 mg/L -∞ h (Algae/water plant, Pseudokirchnerella subcapitata) NOELR value
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1
LC₅₀: 27.9 mg/L 2 d (fish, Poecilia reticulata (Guppy))
EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
NOEC: 5 mg/L -∞ h (fish, Poecilia reticulata (Guppy))
ErC₅₀: 58.5 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 15/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

12.2. Persistence and degradability

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Biodegradation: Yes, rapidly
Remark: Empfohlener Wert der LOG KOW Datenbank
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2
Biodegradation: Yes, rapidly
Remark: Bioakkumulation potentiell möglich, Schädlich für Fische.
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 927-632-8
Biodegradation: Yes, rapidly
Remark: readily biodegradable
butanone CAS No.: 78-93-3 EC No.: 201-159-0
Biodegradation: Yes, rapidly
Hydrocarbons, C10, Aromatics, >1% Naphtalene EC No.: 919-284-0
Biodegradation: Yes, rapidly
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1
Biodegradation: Yes, slowly
Remark: Sudan Marker 455 was poorly biodegradable under the conditions of this test. (GESTIS)

12.3. Bioaccumulative potential

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Log K_{OW}: 0.05
butanone CAS No.: 78-93-3 EC No.: 201-159-0
Log K_{OW}: 0.29
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1
Log K_{OW}: 6.06

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

propan-2-ol CAS No.: 67-63-0 EC No.: 200-661-7
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
Hydrocarbons, C9-C10, containing n-alkanes, isoalkanes, cyclics, with <2% aromatics EC No.: 927-241-2
Results of PBT and vPvB assessment: —
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics EC No.: 927-632-8
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
butanone CAS No.: 78-93-3 EC No.: 201-159-0
Results of PBT and vPvB assessment: —
Hydrocarbons, C10, Aromatics, >1% Naphtalene EC No.: 919-284-0
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
N-Ethyl-N-[2-[1-(2-methylpropoxy)ethoxy]ethyl]-4-phenyldiazenylaniline CAS No.: 34432-92-3 EC No.: 252-021-1
Results of PBT and vPvB assessment: —

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 16/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

14 06 03 *	other solvents and solvent mixtures
------------	-------------------------------------

*: Evidence for disposal must be provided.

Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
------	-----------

Remark:

Изхвърляне съгласно Наредбата за предотвратяване и обезвреждане на отпадъци (VVEA, ehem. TVA) ШВЕЙЦАРИЯ - Код на отпадъците: 1101 - Нехалогенирани разтворители

Waste code packaging

15 01 06	mixed packaging
----------	-----------------

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Completely emptied packages can be recycled.

Other disposal recommendations:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Collect in closed and suitable containers for disposal.

13.2. Additional information

Return to Distributor..

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping name			
FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, LIQUID, N.O.S.)	FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, LIQUID, N.O.S.)	FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, LIQUID, N.O.S.)	FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, LIQUID, N.O.S.)
14.3. Transport hazard class(es)			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
		MARINE POLLUTANT	
14.6. Special precautions for user			
Special Provisions: 640D	Special Provisions: 640D	Special Provisions: 640D	Special Provisions: 640D
Limited quantity (LQ): 1 L	Limited quantity (LQ): 1 L	Limited quantity (LQ): 1L	Limited quantity (LQ): 1L

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 17/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E) Remark: -	Classification code: F1 Remark: -	EmS-No.: F-E, S-E	

14.7. Maritime transport in bulk according to IMO instruments

not determined.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented.

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5a Flammable Liquids, Category 1 or 2
- P5b Flammable liquids
- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 94.1 weight-%

15.1.2. National regulations

[GB] National regulations

Other regulations, restrictions and prohibition regulations

Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)

Regulation 850/2004/EC on persistent organic pollutants (POP)

Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

For abbreviations and acronyms, see ECHA: Guidance on information requirements and chemical safety assessment, Chapter R.20 (list of terms and abbreviations).

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 29 Aug 2022

Print date: 21 Sep 2022

Version: 0.1

FSG Schäfer GmbH

Instandsetzungs-Materialien für Möbeloberflächen



Page 18/18

FSG-Anti-Adhesive Agent, Type TR 12 Plus

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	
Germ cell mutagenicity (<i>Muta. 1B</i>)	H340: May cause genetic defects.	
Carcinogenicity (<i>Carc. 1B</i>)	H350: May cause cancer.	
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure. (central nervous system)	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.